





## Your coffee break just got better

Created with the customers' needs in mind, G-Caffé UNI-Q Touch is equipped with a new, 18" touch display with disability-friendly interface; a smart and innovative display designed to communicate with the Slave vending machine associated to the new G-Caffè UNI-Q Touch machine. Connect a G-Snack Slave machine to the new G-Caffé UNI-Q Touch and provide customers with a full array of snacks to match their hot drinks; the new 18" touch display will collect each multi-purchasing order and guide the users throughout the entire operation while showcasing products offers, nutrition facts and graphic contents of your choice.

HS 7T

## G-Caffè UNI-Q TOUCH ESPRESSO

TECHNICAL SPECIFICATIONS	HS 7T
DIMENSIONS H x W x D (mm)	1830 x 655 x 770
WEIGHT (NET - Standard machine without options)	180 Kg
CUP TYPES	Ø 70-73 mm   Ø 80 mm
CUPS	Up to 750 or Up to 550
STIRRER (90/105/115 mm) pcs	500
NO. OF SELECTIONS	22
PRE-SELECTIONS	1 (sugar)
DISPLAY	18.5" Touch Screen
INGREDIENT CANISTER	6x M size (4.4 I)
WATER FITTING CONNCETION	G 3/4" 2-8 bar (0,2 Mpa - 0,8 Mpa)
PROTOCOL	Executive / MDB
INSTANT HEATER (RATED POWER)	1x 2300W (Espresso) 1x 3200W (Powder)
POWER SUPPLY	220-240 V / 50-60 Hz
POWER CONSUMPTION	134 Wh/L
En aver a consumption in M/b non liter of England diagonal	

OP'	τιο	NAL
<b>U</b> .		

LARGE ESPRESSO BREWER DOUBLE GRINDER CUP SENSOR WATER TANK KIT 20 LT. WATER SOFTENER (FILTER) SPECIAL CODED LOCK (RIELDA) SECURITY CASH BOX SYSTEM TELEMETRY KIT KIT EVA DTS VARIOUS FITTING KITS CUSTOMIZATION

\*Energy consumption in Wh per liter of Espresso dispensed

© Sanden Vendo GmbH

Technical data, images and information provided on this document is intended for informational purposes only; All specification are subject to change without notice.







## Your coffee break just got better

Created with the customers' needs in mind, G-Caffé UNI-Q Touch is equipped with a new, 18" touch display with disability-friendly interface; a smart and innovative display designed to communicate with the Slave vending machine associated to the new G-Caffè UNI-Q Touch machine. Connect a G-Snack Slave machine to the new G-Caffé UNI-Q Touch and provide customers with a full array of snacks to match their hot drinks; the new 18" touch display will collect each multi-purchasing order and guide the users throughout the entire operation while showcasing products offers, nutrition facts and graphic contents of your choice.

HN 7T

## **G-Caffè UNI-Q TOUCH INSTANT**

TECHNICAL SPECIFICATIONS	HN 7T
DIMENSIONS H x W x D (mm)	1830 x 655 x 770
WEIGHT (NET - Standard machine without options)	180 Kg
CUP TYPES	Ø 70-73 mm   Ø 80 mm
CUPS	Up to 750 or Up to 550
STIRRER (90/105/115 mm) pcs	500
NO. OF SELECTIONS	22
PRE-SELECTIONS	1 (sugar)
DISPLAY	18.5" Touch Screen
INGREDIENT CANISTER	8x M size (4.4 l)
WATER FITTING CONNCETION	G 3/4" 2-8 bar (0,2 Mpa - 0,8 Mpa)
PROTOCOL	Executive / MDB
INSTANT HEATER (RATED POWER)	1x 2300W
POWER SUPPLY	220-240 V / 50-60 Hz
POWER CONSUMPTION	134 Wh/L

CUP SENSOR WATER TANK KIT 20 LT. WATER SOFTENER (FILTER) SPECIAL CODED LOCK (RIELDA) SECURITY CASH BOX SYSTEM TELEMETRY KIT KIT EVA DTS VARIOUS FITTING KITS CUSTOMIZATION

\*Energy consumption in Wh per liter of Espresso dispensed

© SandenVendo GmbH

Technical data, images and information provided on this document is intended for informational purposes only; All specification are subject to change without notice.