

GCafè



Enhance your downtime

CaffèUNO is the compact tabletop coffee server designed to fit in any location without compromising on coffee quality; available in black or white monochrome, CaffèUNO is the modern espresso coffee vending server equipped with a large and user-friendly touch display or direct selection panel. One cup, one temperature: ideal for breakfast buffets and meeting rooms, the top-notch heating system installed on CaffèUNO allows for customizing each cup's temperature... (more at our website)

TSC

CaffèUNO "PRO" Espresso - TSC

TECHNICAL SPECIFICATIONS	TSC
DIMENSIONS H x W x D (mm)	770 x 420 x 530
WEIGHT (NET - Standard machine without options)	35 Kg
COFFEE BEANS CANISTER	2.4 kg (hopper)
POWDER CANISTER	2 Large 1 Small
GRINDER	Professional Conical Burr
INTERFACE TOUCH	10" Touch Screen
INTERFACE DIRECT SELECTION	5" Display with 10 Direct Push Button
WATER FITTING CONNCETION	G 3/4" 0.2-8 Bar (0.2 Mpa – 0.8 Mpa)
THERMOFUSE	16 A
PAYMENT SYSTEM PROTOCOL (Option)	Executive / MDB
POWER SUPPLY	220/240 V - 50/60 Hz
ENERGY CONSUMPTION*	134 Wh/L

TOUCH SCREEN LARGE ESPRESSO BREWER DOUBLE GRINDER CUP SENSOR WATER TANK KIT 20 LT. WATER SOFTENER (FILTER) SPECIAL CODED LOCK (RIELDA) PAYMENT SYSTEM BASE CABINET PAYMENT TOWER MODULE VARIOUS FITTING KITS CUSTOMIZED PANEL CUSTOMIZED CABINET COLOUR

OPTIONAL

*Energy consumption in Wh per liter of espresso dispensed

© SandenVendo GmbH

Technical data, images and information provided on this document is intended for informational purposes only; All specification are subject to change without notice.



GCafè



Enhance your downtime

CaffèUNO is the compact tabletop coffee server designed to fit in any location without compromising on coffee quality; available in black or white monochrome, CaffèUNO is the modern espresso coffee vending server equipped with a large and user-friendly touch display or direct selection panel. One cup, one temperature: ideal for breakfast buffets and meeting rooms, the top-notch heating system installed on CaffèUNO allows for customizing each cup's temperature... (more at our website)

TSE

CaffèUNO - Espresso - TSE

TECHNICAL SPECIFICATIONS	TSE
DIMENSIONS H x W x D (mm)	660 x 420 x 530
WEIGHT (NET - Standard machine without options)	35 Kg
COFFEE BEANS CANISTER	1.2 kg
POWDER CANISTER	2 Large 1 Small
GRINDER	Professional Conical Burr
INTERFACE TOUCH	10" Touch Screen
INTERFACE DIRECT SELECTION	5" Display with 10 Direct Push Button
WATER FITTING CONNCETION	G 3/4" 0.2-8 Bar (0.2 Mpa – 0.8 Mpa)
THERMOFUSE	16 A
PAYMENT SYSTEM PROTOCOL (Option)	Executive / MDB
POWER SUPPLY	220/240 V - 50/60 Hz
ENERGY CONSUMPTION*	134 Wh/L

*Energy consumption in Wh per liter of espresso dispensed

TOUCH SCREEN LARGE ESPRESSO BREWER DOUBLE GRINDER CUP SENSOR WATER TANK KIT 20 LT. WATER SOFTENER (FILTER) SPECIAL CODED LOCK (RIELDA) PAYMENT SYSTEM BASE CABINET PAYMENT TOWER MODULE VARIOUS FITTING KITS CUSTOMIZATION CUSTOMIZED PANEL CUSTOMIZED CABINET COLOUR

OPTIONAL

© Sanden Vendo GmbH

Technical data, images and information provided on this document is intended for informational purposes only; All specification are subject to change without notice.



GCafè



Enhance your downtime

CaffèUNO is the compact tabletop coffee server designed to fit in any location without compromising on coffee quality; available in black or white monochrome, CaffèUNO is the modern espresso coffee vending server equipped with a large and user-friendly touch display or direct selection panel. One cup, one temperature: ideal for breakfast buffets and meeting rooms, the top-notch heating system installed on CaffèUNO allows for customizing each cup's temperature... (more at our website)

TSH

CaffèUNO - Instant TSH

TECHNICAL SPECIFICATIONS	TSH
DIMENSIONS H x W x D (mm)	660 x 420 x 530
WEIGHT (NET - Standard machine without options)	35 Kg
POWDER CANISTER	2 Large 2 Medium 1 Small
INTERFACE TOUCH	10" Touch Screen
INTERFACE DIRECT SELECTION	5" Display with 10 Direct Push Button
WATER FITTING CONNCETION	G 3/4" 0.2-8 Bar (0.2 Mpa – 0.8 Mpa)
THERMOFUSE	16 A
PAYMENT SYSTEM PROTOCOL (Option)	Executive / MDB
POWER SUPPLY	220/240 V - 50 /60 Hz
ENERGY CONSUMPTION*	134 Wh/L

 $^{*}\mbox{Energy}$ consumption in Wh per liter of espresso dispensed

OPTIONAL

TOUCH SCREEN LARGE ESPRESSO BREWER CUP SENSOR WATER TANK KIT 20 LT. WATER SOFTENER (FILTER) SPECIAL CODED LOCK (RIELDA) PAYMENT SYSTEM PAYMENT TOWER MODULE VARIOUS FITTING KITS CUSTOMIZATION CUSTOMIZED PANEL CUSTOMIZED CABINET COLOUR

© SandenVendo GmbH

Technical data, images and information provided on this document is intended for informational purposes only; All specification are subject to change without notice.