



Outdoor snacking? Solved!

Crafted with premium materials and equipped with top-notch technological features, G-Snack Outdoor represents the safest and smartest way to pursue your automatic outdoor vending business. Backed by SandenVendo's expertise in thermo-dynamics and cooling systems, G-Snack Outdoor comes with a thermal-magnetic circuit breaker and a temperature controller specially designed to operate under severe weather conditions. IP34 waterproof certified, this model comes with a heated anti-condensation glass, a new anti-vandal design and a smart LED illumination system.

SMX OD

G-Snack Ten (X) Outdoor

TECHNICAL SPECIFICATIONS

	SMX OD
DIMENSIONS H x W x D (mm)	1900 x 1200 x 1010
WEIGHT (NET - Standard machine without options)	400 kg
NO. OF SELECTIONS PER SHELF	10
NO. OF SHELVES	Standard 6 / max. 7
NO. OF SELECTIONS	max. 70
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
INTERNAL TEMPERATURE RANGE	+2°C up to +18°C
AMBIENT TEMPERATURE RANGE	-15°C up to +32°C
COOLING UNIT	HCD
POWER SUPPLY	230/240 V - 50/60 Hz
MAX. POWER CONSUMPTION	450 W
ENERGY CLASS	E (Cat. 2) E (Cat. 3) E (Cat. 4)
ENERGY CONSUMPTION - kWh/annum	1553 (Cat. 2) 1836 (Cat. 3) 1714 (Cat. 4)

OPTIONAL

SPEEDY LIFT
E-LABELING
ROTARY & BELT SYSTEM
KIT SANDWICH / BAGUETTE
MOTORIZED LOCK DELIVERY EYELET
SPECIAL CODED LOCK (RIELDA)
SECURITY CASH BOX SYSTEM
WALL/FLOOR FIXING KIT
PAYMENT SYSTEM
KIT EVA DTS
VARIOUS FITTING KITS
CUSTOMIZATION
CUSTOMIZED CABINET COLOUR



Outdoor snacking? Solved!

Crafted with premium materials and equipped with top-notch technological features, G-Snack Outdoor represents the safest and smartest way to pursue your automatic outdoor vending business. Backed by SandenVendo's expertise in thermo-dynamics and cooling systems, G-Snack Outdoor comes with a thermal-magnetic circuit breaker and a temperature controller specially designed to operate under severe weather conditions. IP34 waterproof certified, this model comes with a heated anti-condensation glass, a new anti-vandal design and a smart LED illumination system.

SM8 OD

G-Snack Eight (VIII) Outdoor

TECHNICAL SPECIFICATIONS

	SM8 OD
DIMENSIONS H x W x D (mm)	1900 x 1030 x 1010
WEIGHT (NET - Standard machine without options)	350 Kg
NO. OF SELECTIONS PER SHELF	8
NO. OF SHELVES	Standard 6 / Max. 7
NO. OF SELECTIONS	Max. 56
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
INTERNAL TEMPERATURE RANGE	+2°C up to +18°C
AMBIENT TEMPERATURE RANGE	-15°C up to +32°C
COOLING UNIT	HCD
INTERNAL TEMPERATURE RANGE	+2°C up to +18°C
POWER SUPPLY	230/240 V - 50/60 Hz
MAX. POWER CONSUMPTION	450 W
ENERGY CLASS	E (Cat. 2) E (Cat. 3) E (Cat. 4)
ENERGY CONSUMPTION - kWh/annum	1232 (Cat. 2) 1619 (Cat. 3) 1414 (Cat. 4)

OPTIONAL

SPEEDY LIFT
E-LABELING
ROTARY & BELT SYSTEM
KIT SANDWICH / BAGUETTE
MOTORIZED LOCK DELIVERY EYELET
SPECIAL CODED LOCK (RIELDA)
SECURITY CASH BOX SYSTEM
WALL/FLOOR FIXING KIT
PAYMENT SYSTEM
KIT EVA DTS
VARIOUS FITTING KITS
CUSTOMIZATION
CUSTOMIZED CABINET COLOUR



Outdoor snacking? Solved!

Crafted with premium materials and equipped with top-notch technological features, G-Snack Outdoor represents the safest and smartest way to pursue your automatic outdoor vending business. Backed by SandenVendo's expertise in thermo-dynamics and cooling systems, G-Snack Outdoor comes with a thermal-magnetic circuit breaker and a temperature controller specially designed to operate under severe weather conditions. IP34 waterproof certified, this model comes with a heated anti-condensation glass, a new anti-vandal design and a smart LED illumination system.

SM6 OD

G-Snack Six (VI) Outdoor

TECHNICAL SPECIFICATIONS

	SM6 OD
DIMENSIONS H x W x D (mm)	1900 x 890 x 1010
WEIGHT (NET - Standard machine without options)	325 kg
NO. OF SELECTIONS PER SHELF	6
NO. OF SHELVES	Standard 6 / Max. 7
NO. OF SELECTIONS	Max. 42
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
INTERNAL TEMPERATURE RANGE	+2°C up to +18°C
AMBIENT TEMPERATURE RANGE	-15°C up to +32°C
COOLING UNIT	HCD
POWER SUPPLY	230/240 V - 50/60 Hz
MAX. POWER CONSUMPTION	450 W
ENERGY CLASS	E (Cat. 2) E (Cat. 3) E (Cat. 4)
ENERGY CONSUMPTION - kWh/annum	1280 (Cat. 2) 1518 (Cat. 3) 1545 (Cat. 4)

OPTIONAL

SPEEDY LIFT
E-LABELING
ROTARY & BELT SYSTEM
KIT SANDWICH / BAGUETTE
MOTORIZED LOCK DELIVERY EYELET
SPECIAL CODED LOCK (RIELDA)
SECURITY CASH BOX SYSTEM
WALL/FLOOR FIXING KIT
PAYMENT SYSTEM
KIT EVA DTS
VARIOUS FITTING KITS
CUSTOMIZATION
CUSTOMIZED CABINET COLOUR