



Proper snacking attitude

Backed by SandenVendo's expertise in thermo-dynamics and cooling technologies, G-Snack Standard features all the advanced software and technology from the Design line, delivering top performance at an affordable price. Spacious and versatile as every G-Snack model, the new G-Snack Standard XII model can accommodate up to 84 selections including a vast assortment of bulk-size and Extra-Vending merchandise thanks to an extremely flexible tray configuration system and a new speedy elevator, turning this automatic vending machine into a mini-market open 24/7.

SLL

G-Snack Standard SLL Twelve (XII) Master

TECHNICAL SPECIFICATIONS

TECHNICAL SPECIFICATIONS	SLL
DIMENSIONS H x W x D (mm)	1830* x 1290 x 900
WEIGHT (NET - Standard machine without options)	410 Kg
NO. OF SELECTIONS PER SHELF	12 (6 + 6)
NO. OF SHELVES	Standard 6 / Max. 7
NO. OF SELECTIONS	Max. 84
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
INTERNAL TEMPERATURE RANGE	+2°C up to +18°C
CLIMATE CLASS	ST (+16°C up to +38°C)
COOLING UNIT	HCD
POWER SUPPLY	230/240 V - 50/60 Hz
MAX. POWER CONSUMPTION	350 W
ENERGY CLASS	C (Cat. 2) C (Cat. 3) C (Cat. 4)
ENERGY CONSUMPTION - kWh/annum	837 (Cat. 2) 992 (Cat. 3) 1063 (Cat. 4)

*With adjustable feet

OPTIONAL

E-LABELING
 ROTARY & BELT SYSTEM
 KIT SANDWICH / BAGUETTE
 SPECIAL CODED LOCK (RIELDA)
 SAFETY SLIDE COIN INSERT
 SECURITY CASH BOX SYSTEM
 WALL/FLOOR FIXING KIT
 PAYMENT SYSTEM
 KIT EVA DTS
 VARIOUS FITTING KITS
 CUSTOMIZATION



Proper snacking attitude

Backed by SandenVendo's expertise in thermo-dynamics and cooling technologies, G-Snack Standard features all the advanced software and technology from the Design line, delivering top performance at an affordable price. Spacious and versatile as every G-Snack model, the new G-Snack Standard XII model can accommodate up to 84 selections including a vast assortment of bulk-size and Extra-Vending merchandise thanks to an extremely flexible tray configuration system and a new speedy elevator, turning this automatic vending machine into a mini-market open 24/7.

SMX

G-Snack Standard Ten (X) Master

TECHNICAL SPECIFICATIONS

SMX

DIMENSIONS H x W x D (mm)	1830*x 1125 x 845
WEIGHT (NET - Standard machine without options)	340 Kg
NO. OF SELECTIONS PER SHELF	10
NO. OF SHELVES	Standard 6 / Max. 7
NO. OF SELECTIONS	Max. 70
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
INTERNAL TEMPERATURE RANGE	+2°C up to +18°C
CLIMATE CLASS	ST (+16°C up to +38°C)
COOLING UNIT	HCD
POWER SUPPLY	230/240 V - 50/60 Hz
MAX. POWER CONSUMPTION	350 W
ENERGY CLASS	C (Cat. 2) C (Cat. 3) C (Cat. 4)
ENERGY CONSUMPTION - kWh/annum	694 (Cat. 2) 869 (Cat. 3) 925 (Cat. 4)

*With adjustable feet

OPTIONAL

SPEEDY LIFT
E-LABELING
ROTARY & BELT SYSTEM
KIT SANDWICH / BAGUETTE
MOTORIZED LOCK DELIVERY EYELET
SPECIAL CODED LOCK (RIELDA)
LOCK PROTECTION
SAFETY SLIDE COIN INSERT
SECURITY CASH BOX SYSTEM
ROOF KIT
WALL/FLOOR FIXING KIT
PAYMENT SYSTEM
KIT EVA DTS
VARIOUS FITTING KITS
CUSTOMIZATION
CUSTOMIZED CABINET COLOUR



Proper snacking attitude

Backed by SandenVendo's expertise in thermo-dynamics and cooling technologies, G-Snack Standard features all the advanced software and technology from the Design line, delivering top performance at an affordable price. Spacious and versatile as every G-Snack model, the new G-Snack Standard XII model can accommodate up to 84 selections including a vast assortment of bulk-size and Extra-Vending merchandise thanks to an extremely flexible tray configuration system and a new speedy elevator, turning this automatic vending machine into a mini-market open 24/7.

SM8

G-Snack Standard Eight (VIII) Master

TECHNICAL SPECIFICATIONS

SM8

DIMENSIONS H x W x D (mm)	1830*x 980 x 845
WEIGHT (NET - Standard machine without options)	310 Kg
NO. OF SELECTIONS PER SHELF	8
NO. OF SHELVES	Standard 6 / Max. 7
NO. OF SELECTIONS	Max. 56
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
INTERNAL TEMPERATURE RANGE	+2°C up to +18°C
CLIMATE CLASS	ST (+16°C up to +38°C)
COOLING UNIT	HCD
POWER SUPPLY	230 V / 50 Hz
MAX. POWER CONSUMPTION	350 W
ENERGY CLASS	C (Cat. 2) C (Cat. 3) C (Cat. 4)
ENERGY CONSUMPTION - kWh/annum	681 (Cat. 2) 849 (Cat. 3) 878 (Cat. 4)

*With adjustable feet

OPTIONAL

SPEEDY LIFT
E-LABELING
ROTARY & BELT SYSTEM
KIT SANDWICH / BAGUETTE
MOTORIZED LOCK DELIVERY EYELET
SPECIAL CODED LOCK (RIELDA)
LOCK PROTECTION
SAFETY SLIDE COIN INSERT
SECURITY CASH BOX SYSTEM
ROOF KIT
WALL/FLOOR FIXING KIT
PAYMENT SYSTEM
KIT EVA DTS
VARIOUS FITTING KITS
CUSTOMIZATION
CUSTOMIZED CABINET COLOUR



Proper snacking attitude

Backed by SandenVendo's expertise in thermo-dynamics and cooling technologies, G-Snack Standard features all the advanced software and technology from the Design line, delivering top performance at an affordable price. Spacious and versatile as every G-Snack model, the new G-Snack Standard XII model can accommodate up to 84 selections including a vast assortment of bulk-size and Extra-Vending merchandise thanks to an extremely flexible tray configuration system and a new speedy elevator, turning this automatic vending machine into a mini-market open 24/7.

SM6

G-Snack Standard Six (VI) Master

TECHNICAL SPECIFICATIONS

SM6

DIMENSIONS H x W x D (mm)	1830*x 830 x 845
WEIGHT (NET - Standard machine without options)	275 Kg
NO. OF SELECTIONS PER SHELF	6
NO. OF SHELVES	Standard 6 / Max. 7
NO. OF SELECTIONS	Max. 42
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
INTERNAL TEMPERATURE RANGE	+2°C up to +18°C
CLIMATE CLASS	ST (+16°C up to +38°C)
COOLING UNIT	HCD
POWER SUPPLY	230/240 V - 50/60 Hz
MAX. POWER CONSUMPTION	350 W
ENERGY CLASS	C (Cat. 2) C (Cat. 3) C (Cat. 4)
ENERGY CONSUMPTION - kWh/annum	629 (Cat. 2) 798 (Cat. 3) 793 (Cat. 4)

*With adjustable feet

OPTIONAL

SPEEDY LIFT
E-LABELING
ROTARY & BELT SYSTEM
KIT SANDWICH / BAGUETTE
MOTORIZED LOCK DELIVERY EYELET
SPECIAL CODED LOCK (RIELDA)
LOCK PROTECTION
SAFETY SLIDE COIN INSERT
SECURITY CASH BOX SYSTEM
ROOF KIT
WALL/FLOOR FIXING KIT
PAYMENT SYSTEM
KIT EVA DTS
VARIOUS FITTING KITS
CUSTOMIZATION
CUSTOMIZED CABINET COLOUR